AG Gases and Equipment Ltd Unit 1a, Britannic Works, Broom Street, Hanley, Stoke-on-Trent, England, ST1 2ER Company No. 10667218 VAT No. 207268317 Founded 13/3/2017 Office: +44(0)1782616611 Fax: +44(0) 1782616610 sales@agequip.co.uk



60 Litre Aluminium Non-Refillable Cylinder

Specifications

Gas volume: 60 litres Water volume: 1.6 litres Filling pressure: 500psi (34 Bar) Cylinder material: Aluminium Valve: C10 valve (5/8"-18) Stainless Steel Weight: 1.19Kg Height: 365mm Diameter: 90mm

Manufacturer Standards

Cylinder made to ISO 7866, valve made to ISO 10297. Mixes manufactured gravimetrically to ISO 6142.

Equipment

- Cylinder valve compatible with all major manufacturers regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand Flow Regulator (ODFR for non-reactive, H2S and SO2 mixtures)
- Variflow regulator (non-reactive gases)

Mixture Tolerances

Calibration gas mixtures are made and certified to:

Concentration	Preparation	Certification
Range	Tolerance	Accuracy
<1ppm	40%	5%
1 to 9.9ppm	20%	5%
10 to 99ppm	10%	2%
100ppm to 0.99%	10%	2%
>1%	5%	2%



We recommend using our **Fixed Flow Regulator** for this cylinder:

